

VARNISHES & COATINGS



P000011118

BIO OVERPRINT MATT VARNISH

SERIES

BIO OVERPRINT MATT VARNISH is a sheetfed offset varnish that provides high resistance to printing while delivering a matt effect. This transparent varnish has low odour and minimal colour and can be applied in spot or full coverage, either wet-on-wet (in-line) or wet-on-dry. Formulated with vegetable oils and free from cobalt driers.

Product features



Printing behaviour

- Suitable for perfecting machines
- · Suitable for in-line and off-line printing
- High rub resistance
- Quick oxidative drying
- Suitable for post laser printing
- · Ideal for paper and cardboard
- Not suitable for food packaging printing without a functional barrier

Martínez Ayala S.A. Polígono Industrial El Saladar C/ La Higuera, 28 (30.850) Totana, Murcia - España Tel: +34 968 41 80 30

info@ma-inks.com www.ma-inks.com



.

TECHNICAL DATA SHEET



Recommendations

- **Cleaning**: it is recommended to clean the rollers at long stops as well as to apply an anti-skin spray in the ink duct.
- Storage: store at temperatures between 20-25
 °C. Avoid the direct exposure to light and heat sources. Once opened, it is recommended to add a layer of anti-drying spray to avoid the possible appearance of skin. A well-conditioned and clean work environment ease the good behaviour of all the components during the printing process. BIO OVERPRINT MATT VARNISH does not have an expiry date in the short or medium term.

Martínez Ayala S.A. Polígono Industrial El Saladar C/ La Higuera, 28 (30.850) Totana, Murcia - España Tel: +34 968 41 80 30

info@ma-inks.com www.ma-inks.com



The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Martinez Ayala's knowledge and belief. No liability for any errors, facts or opinions will be accepted. Customers must verify and test by themselves the suitability of this product for their application. No liability for any loss as a result of any person placing reliance on any material contained herein will be accepted.

......

EN

2/2