

C000001154

# UV FLEXO GLOSS BVG 80 PLUS GHS STAMPING

### **SERIES**

UV FLEXO GLOSS BVG 80 PLUS GHS STAMPING. UV curing varnish for printing on UV Flexo coaters, offering a gloss finish and excellent aesthetic quality, designed for applications on paper, cardboard and various synthetic substrates.

## **Product features**

Gloss Rub resistance Slippage Curing speed Values from 1 (lower range) to 7 (highest range)

# **Printing behaviour**

- Suitable for all types of paper and cardboard substrates, and for certain types of PE, PP, PVC and PET foils with chemical or corona counteracting and for pretreated aluminum foils.
- Glueable, suitable for cold or hot foil and varnishable.
- · Not suitable for food packaging printing without functional barrier.

Martínez Ayala S.A. Polígono Industrial El Saladar C/ La Higuera, 28 (30.850) Totana, Murcia - España Tel: +34 968 41 80 30

info@ma-inks.com www.ma-inks.com







1/2



### Recommendations

- Pre-testing is always recommended.
- · Shake well before use.
- Storage: Store at a temperature between 15 20°C and avoid direct exposure to light and heat, preferably in a dark room. A conditioned and clean working environment facilitates the good performance of all components during printing. UV FLEXO GLOSS BVG 80 PLUS GHS STAMPING has a shelf life of 12 months after date of manufacture.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Martinez Ayala's knowledge and belief. No liability for any errors, facts or opinions will be accepted. Customers must verify and test by themselves the suitability of this product for their application. No liability for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Martínez Ayala S.A. Polígono Industrial El Saladar C/ La Higuera, 28 (30.850) Totana, Murcia - España Tel: +34 968 41 80 30

info@ma-inks.com www.ma-inks.com





