

C000000422

UV FLEXO GLOSS VARNISH NW-2000

SERIES

UV FLEXO GLOSS VARNISH NW-2000.

UV curing varnish for printing on UV Flexo coaters, offering a high gloss finish and excellent aesthetic quality, designed for applications on paper, board and various synthetic substrates.

Product features

Rub resistance

Gloss

Flexibility

Curing speed

Values from 1 (lower range) 1 2 3 4 5 6 to 7 (highest range)

Printing behaviour

- Suitable for all types of paper and cardboard substrates
- Non-glueable
- Non-stampable
- High gloss effect
- Not suitable for food packaging printing without a functional barrier

Martínez Ayala S.A. Polígono Industrial El Saladar C/ La Higuera, 28 (30.850) Totana, Murcia - España Tel: +34 968 41 80 30

info@ma-inks.com www.ma-inks.com









Recommendations

- Pre-testing is always recommended.
- Use on substrates with grammage above 115 gsm. The use on lower grammages may cause distortion or curling.
- Shake well before use.
- · Do not mix with other varnishes.
- Storage: Store at a temperature between 5 30°C and avoid direct exposure to light and heat. A conditioned and clean working environment facilitates the proper functioning of all components during printing, UV FLEXO GLOSS VARNISH NW-2000 has a shelf life of 12 months after manufacture. Once opened, use as soon as possible

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Martinez Ayala's knowledge and belief. No liability for any errors, facts or opinions will be accepted. Customers must verify and test by themselves the suitability of this product for their application. No liability for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Martínez Ayala S.A. Polígono Industrial El Saladar C/ La Higuera, 28 (30.850) Totana, Murcia - España Tel: +34 968 41 80 30

info@ma-inks.com www.ma-inks.com





