

UV PACK LM

SERIES

Series of low migration, low odour, ultraviolet curing offset inks specially formulated for food packaging printing on non-absorbent substrates and also suitable for absorbent substrates.

Printing behaviour

- Excellent water-ink balance
- Good adhesion and high flexibility of the printed layer
- Total laser resistance after UV curing
- Suitable for substrates: coated and uncoated paper, corona treated vinyl, pretreated plastics, coated metals
- · Suitable for IML (In Mould Label) printing

Recommendations

- Pre-testing is always recommended.
- Excessive exposure to UV light can affect the fluorescent effect. It is recommended to use the minimum UV lamp energy for curing the inks.
- Optimal rub resistance will be obtained 24 hours after printing.
- Storage: Store at a temperature between 5 -25°C and avoid direct exposure to light and heat.
- Shelf life: 12 months from its date of manufacture.

Martínez Ayala S.A. Polígono Industrial El Saladar C/ La Higuera, 28 (30.850) Totana, Murcia - España Tel: +34 968 41 80 30

info@ma-inks.com www.ma-inks.com







ΕN



Technical data

	LIGHT (WS)	ALCOHOL	NITRO	ALKALI
	Fastness properties in accordance with ISO 12040 and ISO 2836			
UV PACK LM PROCESS YELLOW	5	+	+	+
UV PACK LM PROCESS MAGENTA	5	+	+	-
UV PACK LM PROCESS CYAN	8	+	+	+
UV PACK LM PROCESS BLACK	8	+	+	+
	UV PACK LM PROCESS MAGENTA UV PACK LM PROCESS CYAN	UV PACK LM PROCESS YELLOW 5 UV PACK LM PROCESS MAGENTA 5 UV PACK LM PROCESS CYAN 8	Fastness properties in accord. UV PACK LM PROCESS YELLOW 5 + UV PACK LM PROCESS MAGENTA 5 + UV PACK LM PROCESS CYAN 8 +	Fastness properties in accordance with ISO 12040 UV PACK LM PROCESS YELLOW 5

Regulatory

- This range accomplishes with EuPIA exclusion list for printing inks and related products, as well as with the heavy metals' limits laid down in the Directive 94/62/EC.
- Formulated according to REACH and Swiss Ordinance.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Martinez Ayala's knowledge and belief. No liability for any errors, facts or opinions will be accepted. Customers must verify and test by themselves the suitability of this product for their application. No liability for any loss as a result of any person placing reliance on any material contained herein will be accepted

Martínez Ayala S.A. Polígono Industrial El Saladar C/ La Higuera, 28 (30.850) Totana, Murcia - España Tel: +34 968 41 80 30

info@ma-inks.com www.ma-inks.com





