



C000001108-0110

UV SCREEN COATING FLAT GLOSS HIGH VISCOSITY

SERIES

UV curing varnish for flat screen printing, formulated with benzophenone-free raw materials that offers a high gloss finish and fast drying. It is suitable for application on all types of paper and cardboard and certain plastic substrates.

Product features



Values from 1 (lower range)
to 7 (highest range)

1 2 3 4 5 6 7

Printing behaviour

- It can be applied on all types of paper and cardboard and on certain corona treated plastic substrates. It is recommended to always test for adhesion before printing.
- High viscosity (100-120 seconds at 21°C).
- This varnish is not suitable for food applications unless an appropriate risk analysis demonstrates that its use is safe.
- Ready for print at optimum viscosity.
- Formulated without benzophenone.
- High gloss varnish.
- Excellent rub resistance.
- Fast drying.

Martínez Ayala S.A.
Polígono Industrial El Saladar
C/ La Higuera, 28
(30.850) Totana, Murcia - España
Tel: +34 968 41 80 30

info@ma-inks.com
www.ma-inks.com





Recommendations

- Pre-testing is always recommended.
- UV varnishes should be kept in stock at temperatures between 15 - 25°C and should not be exposed to direct sunlight. If possible, store the varnish in a dark room.
- **Shelf life:** 12 months from date of manufacture.
- Shake well before use.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Martínez Ayala's knowledge and belief. No liability for any errors, facts or opinions will be accepted. Customers must verify and test by themselves the suitability of this product for their application. No liability for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Martínez Ayala S.A.
Polígono Industrial El Saladar
C/ La Higuera, 28
(30.850) Totana, Murcia - España
Tel: +34 968 41 80 30

info@ma-inks.com
www.ma-inks.com

